

Novedad



349,20 €
379,20 €
448,80 €
489,60 €
549,60 €
598,80 €

TECHNICAL DATA

Model	3 kW	4 kW	5 kW
Reference	PC-NANO-A3	PC-NANO-A4	PC-NANO-A5
Pool volume (m³)	10 - 21 m³	15 - 28 m³	20 - 35 m³
Air 26°C Capacity (W)	3010	4200	5010
Water 26°C Consumption (W)	540	760	910
Hygro 80% COP	5.61	5.50	5.50
Air 15°C Capacity (W)	2210	3100	4030
Eau 26°C Consumption (W)	540	760	1000
Hygro 70% COP	4.09	4.08	4.03
Electricity supply	Mono 220-240V / 50Hz		
Max Power (W)	930	1200	1500
Max current (A)	4.15	5.32	6.65
Heating temperature range	15°C / 40°C		
Operating range	8°C / 43°C		
Flow (m³/h)	1.3	2	2.5
Refrigerant	R32		
Package dimensions (mm)	460 x 370 x 415		
Dimensions (mm)	400 x 280 x 385		
Net / Gross weight (kg)	18 / 20	24 / 28	26 / 30
Noise level at 1 m (dB(A))	< 53	< 55	< 56
Noise level at 4 m (dB(A))	< 43	< 45	< 46
Noise level at 10 m (dB(A))	< 32	< 35	< 36
Compressor type	Rotative		
Compressor brand	Toshiba		
Heat exchanger	Twisted Tech® Titane		
Function	Heating		
Load losses (mCE)	0.8		

DONNÉES TECHNIQUES

Model	3 kW	4 kW	5 kW
Reference	PC-NANO-A3R	PC-NANO-A4R	PC-NANO-A5R
Pool volume (m³)	10 - 21 m³	15 - 28 m³	20 - 35 m³
Air 26°C Capacity (W)	3000	4 200	5 010
Water 26°C Consumption (W)	600	810	990
Hygro 80% COP	5	5,19	5,03
Air 15°C Capacity (W)	2 200	3 100	4 030
Eau 26°C Consumption (W)	560	760	1000
Hygro 70% COP	3,93	4,08	4,03
Electricity supply	Mono 220-240V / 50Hz		
Max Power (W)	900	1200	1500
Max current (A)	3,99	5,32	6,65
Heating temperature range	15°C / 40°C		
Cooling temperature range	8°C / 28°C		
Operating range	-5°C / 43°C		
Flow (m³/h)	2	2	2,5
Refrigerant	R32		
Package dimensions (mm)	460 x 370 x 415		
Dimensions (mm)	400 x 280 x 385		
Net / Gross weight (kg)	18 / 20	25 / 29	26 / 30
Noise level at 1 m (dB(A))	< 53	< 55	< 56
Noise level at 4 m (dB(A))	< 43	< 45	< 46
Noise level at 10 m (dB(A))	< 33	< 35	< 36
Compressor type	Rotative		
Compressor brand	Toshiba		
Heat exchanger	Twisted Tech® Titane		
Function	Heating / Cooling		
Load losses (mCE)	0,8		