HAYWARD

EXPERT LINE

AquaRite® NEO



As defined by EN 17645.
Go to report pages to see the complete detail by item.

TH TOTALLY HAYWARD

3 YEARS OF WARRANTY STANDARD + 4 TH 8000 HOURS Cell

MADE IN EU


BUILT FOR TODAY, READY FOR THE FUTURE

- **Salt chlorinator** with control of standard water parameters: pH, redoX and temperature
- **Remote management** of the water quality thanks to Wi-Fi connection or Ethernet connection kits as an option
- **Transparent cell** to provide visual control of chlorine production
- **pH, redoX and temperature kits** available as an option
- **Easy installation** of accessories



INCLUDED

- Chlorine generation
- Touch Screen 4.3"
- Salt water & Sea water compatible
- Modbus protocol



Manage all your parameters using the free custom-designed app **Hayward® Poolwatch**

	Description	AQR-NEO-16	AQR-NEO-22	AQR-NEO-33	AQR-NEO-50
AQUARITE® NEO	Maximum production g Cl/h	16 g/h	22 g/h	33 g/h	50 g/h
	Average volume of the pool	75 m³	100 m³	150 m³	200 m³
	Salt concentration	From 3 g to 100 g of NaCl			
	Display	4.3" Touch Screen			
	Choice of languages	ES (Spanish) - EN (English) - FR (French) - DE (German) - IT (Italian) - TR (Turkish) - CS (Czech) - PT (Portuguese) - NL (Dutch) - PL (Polish) - HU (Hungarian) - RU (Russian) - HR (Croatian)			
	Power supply	230 VAC 50/60 Hz			
	Dimensions	254 x 298 x 115 mm			
	Box	Black and white ABS flame retardant plastic			
	Output	7 V 15.5 A	6.5 V 15.5 A	9.5 V 15 A	12 V 15 A
	Consumption	120 W	130 W	150 W	190 W
	Self-cleaning	By polarity inversion, can be configured by the installer			
	Flow detection	●	●	●	●
	Gas detection	●	●	●	No
	Alarms	Low production / No flow / AL3 for injection of pH adjuster / AL4 for cell configurable			
	Maximum temperature	45 °C			
TRANSPARENT CELL	Hydrolysis cell	4 titanium plates	5 titanium plates	7 titanium plates	10 titanium plates
	Minimum flow	5 m³/h	7 m³/h	9 m³/h	9 m³/h
	Dimensions of the plates	200 x 45 mm	200 x 45 mm	200 x 45 mm	400 x 45 mm
	Cell holder material	Transparent PVC plastic			
	Cell attachment method	Threaded for easy installation of the cell			
	Flexible hose connector diameter	63 mm			
	Cell dimensions	355 x 305 x 305 mm			520 x 305 x 305 mm
	Cell cable	(3 x 4) x 1.5 m (extension cable available, refer to the catalogue of spare parts)			(2 x 4) x 1.5 m
	Maximum pressure	4 kg/cm²			
	Maximum temperature	45 °C			
OPTIONS AVAILABLE	pH kit	BPENG-OPTION-PH (premium plastic probe) / BGKBPER (glass probe) - (peristaltic pump 1.5 L/h)			
	ORP kit	E-OPTION-REDOX (premium plastic probe) / EG (glass probe)			
	Temperature kit	T-OPTION-TEMP			
	Wi-Fi module	RS4WI-OPTION-W			
	Ethernet module	RS4NET-OPTION-L			
	Pool anode	KV02			


Transparent probe holder in PVC included


Flow switch included


Plastic pH kit


ORP probe plastic kit


Temperature kit


Wi-Fi module


Ethernet module