Powerline by HAYWARD

Plug n Clear



As defined by EN 17645.
Go to report pages to see the complete detail by item.

YEARS OF WARRANTY

3 STANDARD 8000 HOURS

Cell

DIY SALT CHLORINATOR: CONNECT, TOUCH, RELAX

- **DIY salt chlorinator:** your swimming pool is disinfected and disinfectant
- Very easy installation (no gluing of the cell required) for a **"plug and play" solution**
- **Intuitive use, the salt chlorinator comes pre-programmed!**
- **Salt chlorinator compatible** with in-ground pools, above-ground pools and spas
- **Large and clearly arranged** user interface
- **Compact and attractive design**, suitable for small technical facilities
- Three tactile control buttons
- **Three operating modes possible** (including a temperature-dependant mode



INCLUDED

- Chlorine production
- Plug & play
- Do It Yourself
- Temperature reading

	Description	PNCLEAR-05	PNCLEAR-10	PNCLEAR-20
ELECTRONIC BOX	Maximum production Cl_2/h	5 g/h	10 g/h	20 g/h
	Salt concentration	3 to 100 g/L		
	Language	Universal		
	Estimated pool volume	20 m³	40 m³	80 m³
	User interface	2 x 11 segments + 3 tactile buttons		
	Power supply	110 - 230 VAC; 50/60 Hz		
	Waterproofing standard	IPX3		
	Dimensions	222 x 174 x 71 mm		
	Material	Fireproof ABS		
	Consumption	45 W	85 W	160 W
	Output	3 A 14 V	5.5 A 15 V	6.5 A 23 V
	Mode	3 programmes: Manuel, Boost, Smart		
	Temperature sensor	Included		
	Safety	Mechanical flow sensor + cell auto-detection		
	Alarms	Flow, low production, temperature < 10 °C		
	Maximum operating temperature	45 °C		
CELL	Titanium plate	4 titanium plates	7 titanium plates	11 titanium plates
	Minimum flow rate	5 m³/h		
	Titanium plate dimensions	120 x 50 mm		
	Support material	Transparent PVC		
	Cell connection diameter	50 mm		
	Cell position	Horizontal		
	Cell mounting	Screwed onto Ø 50 mm pipe		
	Cable length	2 m		
	Maximum pressure	4 kg/cm²		
	Cell operating time	Counter included		
	Self-cleaning	Programmable polarity reversal (6 hours by default)		
	Maximum operating temperature	45 °C		
ACCESSORIES	1.5" connector pack (2 units)	GLX-DIY-CCN15		
	2" connectors pack (2 units)	GLX-DIY-CCN2		
	50 mm glued connector pack (2 units)	SP2700UNKIT50		
	63 mm glued connector pack (2 units)	SP3200UNKIT63		